

Linux Kernel Procfs Guide

Erik (J.A.K.) Mouw
Delft University of Technology
Faculty of Information Technology and Systems

J.A.K.Mouw@its.tudelft.nl
PO BOX 5031
2600 GA
Delft
The Netherlands

Linux Kernel Procfs Guide

by Erik (J.A.K.) Mouw

Copyright © 2001 by Erik Mouw

This documentation is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This documentation is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

For more details see the file COPYING in the source distribution of Linux.

Revision History

Revision 1.0 May 30, 2001

Initial revision posted to linux-kernel

Revision 1.1 June 3, 2001

Revised after comments from linux-kernel

Table of Contents

Preface.....	i
1. Introduction.....	1
2. Managing procfs entries	2
2.1. Creating a regular file.....	2
2.2. Creating a symlink	2
2.3. Creating a device.....	3
2.4. Creating a directory.....	3
2.5. Removing an entry	3
3. Communicating with userland	5
3.1. Reading data.....	5
3.2. Writing data	6
3.3. A single call back for many files.....	6
4. Tips and tricks.....	8
4.1. Convenience functions	8
4.2. Modules.....	8
4.3. Mode and ownership	8
5. Example	10

Preface

This guide describes the use of the procfs file system from within the Linux kernel. The idea to write this guide came up on the #kernelnewbies IRC channel (see <http://www.kernelnewbies.org/>), when Jeff Garzik explained the use of procfs and forwarded me a message Alexander Viro wrote to the linux-kernel mailing list. I agreed to write it up nicely, so here it is.

I'd like to thank Jeff Garzik <jgarzik@mandrakesoft.com> and Alexander Viro <viro@math.psu.edu> for their input, Tim Waugh <twaugh@redhat.com> for his Selfdocbook (<http://people.redhat.com/twaugh/docbook/selfdocbook/>), and Marc Joosen <marc.j@historia.et.tudelft.nl> for proofreading.

This documentation was written while working on the LART computing board (<http://www.lart.tudelft.nl/>), which is sponsored by the Mobile Multi-media Communications (<http://www.mmc.tudelft.nl/>) and Ubiquitous Communications (<http://www.ubicom.tudelft.nl/>) projects.

Erik

Chapter 1. Introduction

The `/proc` file system (procfs) is a special file system in the linux kernel. It's a virtual file system: it is not associated with a block device but exists only in memory. The files in the procfs are there to allow userland programs access to certain information from the kernel (like process information in `/proc/[0-9]+/`), but also for debug purposes (like `/proc/ksyms`).

This guide describes the use of the procfs file system from within the Linux kernel. It starts by introducing all relevant functions to manage the files within the file system. After that it shows how to communicate with userland, and some tips and tricks will be pointed out. Finally a complete example will be shown.

Note that the files in `/proc/sys` are sysctl files: they don't belong to procfs and are governed by a completely different API described in the Kernel API book.

Chapter 2. Managing procfs entries

This chapter describes the functions that various kernel components use to populate the procfs with files, symlinks, device nodes, and directories.

A minor note before we start: if you want to use any of the procfs functions, be sure to include the correct header file! This should be one of the first lines in your code:

```
#include <linux/proc_fs.h>
```

2.1. Creating a regular file

```
struct proc_dir_entry* create_proc_entry(const char* name,  
mode_t mode, struct proc_dir_entry* parent);
```

This function creates a regular file with the name *name*, file mode *mode* in the directory *parent*. To create a file in the root of the procfs, use NULL as *parent* parameter. When successful, the function will return a pointer to the freshly created struct proc_dir_entry; otherwise it will return NULL. Chapter 3 describes how to do something useful with regular files.

Note that it is specifically supported that you can pass a path that spans multiple directories. For example `create_proc_entry("drivers/via0/info")` will create the via0 directory if necessary, with standard 0755 permissions.

If you only want to be able to read the file, the function `create_proc_read_entry` described in Section 4.1 may be used to create and initialise the procfs entry in one single call.

2.2. Creating a symlink

```
struct proc_dir_entry* proc_symlink(const char* name, struct  
proc_dir_entry* parent, const char* dest);
```

This creates a symlink in the procfs directory *parent* that points from *name* to *dest*. This translates in userland to `ln -s dest name`.

2.3. Creating a device

```
struct proc_dir_entry* proc_mknod(const char* name, mode_t mode,
                                struct proc_dir_entry* parent, kdev_t rdev);
```

Creates a device file *name* with mode *mode* in the procfs directory *parent*. The device file will work on the device *rdev*, which can be generated by using the MKDEV macro from `linux/kdev_t.h`. The *mode* parameter *must* contain `S_IFBLK` or `S_IFCHR` to create a device node. Compare with userland `mknod --mode=mode name rdev`.

2.4. Creating a directory

```
struct proc_dir_entry* proc_mkdir(const char* name, struct
                                proc_dir_entry* parent);
```

Create a directory *name* in the procfs directory *parent*.

2.5. Removing an entry

```
void remove_proc_entry(const char* name, struct proc_dir_entry* parent);
```

Removes the entry *name* in the directory *parent* from the procfs. Entries are removed by their *name*, not by the struct `proc_dir_entry` returned by the various create functions. Note that this function doesn't recursively remove entries.

Be sure to free the *data* entry from the struct `proc_dir_entry` before `remove_proc_entry` is called (that is: if there was some *data* allocated, of course). See Section 3.3 for more information on using the *data* entry.

Chapter 3. Communicating with userland

Instead of reading (or writing) information directly from kernel memory, procfs works with *call back functions* for files: functions that are called when a specific file is being read or written. Such functions have to be initialised after the procfs file is created by setting the `read_proc` and/or `write_proc` fields in the struct `proc_dir_entry`* that the function `create_proc_entry` returned:

```
struct proc_dir_entry* entry;  
  
entry->read_proc = read_proc_foo;  
entry->write_proc = write_proc_foo;
```

If you only want to use a the `read_proc`, the function `create_proc_read_entry` described in Section 4.1 may be used to create and initialise the procfs entry in one single call.

3.1. Reading data

The read function is a call back function that allows userland processes to read data from the kernel. The read function should have the following format:

```
int read_func(char* page, char** start, off_t off, int count,  
int* eof, void* data);
```

The read function should write its information into the `page`. For proper use, the function should start writing at an offset of `off` in `page` and write at most `count` bytes, but because most read functions are quite simple and only return a small amount of information, these two parameters are usually ignored (it breaks pagers like `more` and `less`, but `cat` still works).

If the `off` and `count` parameters are properly used, `eof` should be used to signal that the end of the file has been reached by writing 1 to the memory location `eof` points to.

The parameter *start* doesn't seem to be used anywhere in the kernel. The *data* parameter can be used to create a single call back function for several files, see Section 3.3.

The `read_func` function must return the number of bytes written into the *page*.

Chapter 5 shows how to use a read call back function.

3.2. Writing data

The write call back function allows a userland process to write data to the kernel, so it has some kind of control over the kernel. The write function should have the following format:

```
int write_func(struct file* file, const char* buffer, unsigned long count, void* data);
```

The write function should read *count* bytes at maximum from the *buffer*. Note that the *buffer* doesn't live in the kernel's memory space, so it should first be copied to kernel space with `copy_from_user`. The *file* parameter is usually ignored. Section 3.3 shows how to use the *data* parameter.

Again, Chapter 5 shows how to use this call back function.

3.3. A single call back for many files

When a large number of almost identical files is used, it's quite inconvenient to use a separate call back function for each file. A better approach is to have a single call back function that distinguishes between the files by using the *data* field in struct `proc_dir_entry`. First of all, the *data* field has to be initialised:

```
struct proc_dir_entry* entry;
struct my_file_data *file_data;

file_data = kmalloc(sizeof(struct my_file_data), GFP_KERNEL);
entry->data = file_data;
```

The *data* field is a void *, so it can be initialised with anything.

Now that the *data* field is set, the *read_proc* and *write_proc* can use it to distinguish between files because they get it passed into their *data* parameter:

```
int foo_read_func(char *page, char **start, off_t off,
                  int count, int *eof, void *data)
{
    int len;

    if(data == file_data) {
        /* special case for this file */
    } else {
        /* normal processing */
    }

    return len;
}
```

Be sure to free the *data* data field when removing the procfs entry.

Chapter 4. Tips and tricks

4.1. Convenience functions

```
struct proc_dir_entry* create_proc_read_entry(const char* name,  
mode_t mode, struct proc_dir_entry* parent, read_proc_t*  
read_proc, void* data);
```

This function creates a regular file in exactly the same way as `create_proc_entry` from Section 2.1 does, but also allows to set the read function `read_proc` in one call. This function can set the `data` as well, like explained in Section 3.3.

4.2. Modules

If procfs is being used from within a module, be sure to set the `owner` field in the `struct proc_dir_entry` to `THIS_MODULE`.

```
struct proc_dir_entry* entry;  
  
entry->owner = THIS_MODULE;
```

4.3. Mode and ownership

Sometimes it is useful to change the mode and/or ownership of a procfs entry. Here is an example that shows how to achieve that:

```
struct proc_dir_entry* entry;  
  
entry->mode = S_IWUSR | S_IRUSR | S_IRGRP | S_IROTH;  
entry->uid = 0;
```

```
entry->gid = 100;
```

Chapter 5. Example

```
/*
 * procfs_example.c: an example proc interface
 *
 * Copyright (C) 2001, Erik Mouw (J.A.K.Mouw@its.tudelft.nl)
 *
 * This file accompanies the procfs-guide in the Linux kernel
 * source. Its main use is to demonstrate the concepts and
 * functions described in the guide.
 *
 * This software has been developed while working on the LART
 * computing board (http://www.lart.tudelft.nl/), which is
 * sponsored by the Mobile Multi-media Communications
 * (http://www.mmc.tudelft.nl/) and Ubiquitous Communications
 * (http://www.ubicom.tudelft.nl/) projects.
 *
 * The author can be reached at:
 *
 * Erik Mouw
 * Information and Communication Theory Group
 * Faculty of Information Technology and Systems
 * Delft University of Technology
 * P.O. Box 5031
 * 2600 GA Delft
 * The Netherlands
 *
 *
 * This program is free software; you can redistribute
 * it and/or modify it under the terms of the GNU General
 * Public License as published by the Free Software
 * Foundation; either version 2 of the License, or (at your
 * option) any later version.
 *
 * This program is distributed in the hope that it will be
 * useful, but WITHOUT ANY WARRANTY; without even the implied
 * warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
 * PURPOSE. See the GNU General Public License for more
 * details.
 *
 * You should have received a copy of the GNU General Public
 * License along with this program; if not, write to the
 * Free Software Foundation, Inc., 59 Temple Place,
```

```
* Suite 330, Boston, MA 02111-1307 USA
*
*/
#include <linux/module.h>
#include <linux/kernel.h>
#include <linux/init.h>
#include <linux/proc_fs.h>
#include <linux/sched.h>
#include <asm/uaccess.h>

#define MODULE_VERSION "1.0"
#define MODULE_NAME "procfs_example"

#define FOOBAR_LEN 8

struct fb_data_t {
    char name[FOOBAR_LEN + 1];
    char value[FOOBAR_LEN + 1];
};

static struct proc_dir_entry *example_dir, *foo_file,
    *bar_file, *jiffies_file, *tty_device, *symlink;

struct fb_data_t foo_data, bar_data;

static int proc_read_jiffies(char *page, char **start,
                            off_t off, int count,
                            int *eof, void *data)
{
    int len;

    MOD_INC_USE_COUNT;

    len = sprintf(page, "jiffies = %ld\n",
                  jiffies);

    MOD_DEC_USE_COUNT;

    return len;
```

```

}

static int proc_read_foobar(char *page, char **start,
                           off_t off, int count,
                           int *eof, void *data)
{
    int len;
    struct fb_data_t *fb_data = (struct fb_data_t *)data;

    MOD_INC_USE_COUNT;

    len = sprintf(page, "%s = '%s'\n",
                  fb_data->name, fb_data->value);

    MOD_DEC_USE_COUNT;

    return len;
}

static int proc_write_foobar(struct file *file,
                            const char *buffer,
                            unsigned long count,
                            void *data)
{
    int len;
    struct fb_data_t *fb_data = (struct fb_data_t *)data;

    MOD_INC_USE_COUNT;

    if(count > FOOBAR_LEN)
        len = FOOBAR_LEN;
    else
        len = count;

    if(copy_from_user(fb_data->value, buffer, len)) {
        MOD_DEC_USE_COUNT;
        return -EFAULT;
    }

    fb_data->value[len] = '\0';

    MOD_DEC_USE_COUNT;
}

```

```

        return len;
    }

static int __init init_procfs_example(void)
{
    int rv = 0;

    /* create directory */
    example_dir = proc_mkdir(MODULE_NAME, NULL);
    if(example_dir == NULL) {
        rv = -ENOMEM;
        goto out;
    }

    example_dir->owner = THIS_MODULE;

    /* create jiffies using convenience function */
    jiffies_file = create_proc_read_entry("jiffies",
                                         0444, example_dir,
                                         proc_read_jiffies,
                                         NULL);
    if(jiffies_file == NULL) {
        rv = -ENOMEM;
        goto no_jiffies;
    }

    jiffies_file->owner = THIS_MODULE;

    /* create foo and bar files using same callback
     * functions
     */
    foo_file = create_proc_entry("foo", 0644, example_dir);
    if(foo_file == NULL) {
        rv = -ENOMEM;
        goto no_foo;
    }

    strcpy(foo_data.name, "foo");
    strcpy(foo_data.value, "foo");
    foo_file->data = &foo_data;
    foo_file->read_proc = proc_read_foobar;
    foo_file->write_proc = proc_write_foobar;
}

```

```

foo_file->owner = THIS_MODULE;

bar_file = create_proc_entry("bar", 0644, example_dir);
if(bar_file == NULL) {
    rv = -ENOMEM;
    goto no_bar;
}

strcpy(bar_data.name, "bar");
strcpy(bar_data.value, "bar");
bar_file->data = &bar_data;
bar_file->read_proc = proc_read_foobar;
bar_file->write_proc = proc_write_foobar;
bar_file->owner = THIS_MODULE;

/* create tty device */
tty_device = proc_mknod("tty", S_IFCHR | 0666,
                        example_dir, MKDEV(5, 0));
if(tty_device == NULL) {
    rv = -ENOMEM;
    goto no_tty;
}

tty_device->owner = THIS_MODULE;

/* create symlink */
symlink = proc_symlink("jiffies_too", example_dir,
                      "jiffies");
if(symlink == NULL) {
    rv = -ENOMEM;
    goto no_symlink;
}

symlink->owner = THIS_MODULE;

/* everything OK */
printk(KERN_INFO "%s %s initialised\n",
      MODULE_NAME, MODULE_VERSION);
return 0;

no_symlink:
remove_proc_entry("tty", example_dir);
no_tty:
remove_proc_entry("bar", example_dir);

```

```
no_bar:
        remove_proc_entry("foo", example_dir);
no_foo:
        remove_proc_entry("jiffies", example_dir);
no_jiffies:
        remove_proc_entry(MODULE_NAME, NULL);
out:
        return rv;
}

static void __exit cleanup_procfs_example(void)
{
    remove_proc_entry("jiffies_too", example_dir);
    remove_proc_entry("tty", example_dir);
    remove_proc_entry("bar", example_dir);
    remove_proc_entry("foo", example_dir);
    remove_proc_entry("jiffies", example_dir);
    remove_proc_entry(MODULE_NAME, NULL);

    printk(KERN_INFO "%s %s removed\n",
           MODULE_NAME, MODULE_VERSION);
}

module_init(init_procfs_example);
module_exit(cleanup_procfs_example);

MODULE_AUTHOR("Erik Mouw");
MODULE_DESCRIPTION("procfs examples");

EXPORT_NO_SYMBOLS;
```